

MOVE

Upper

Outsole

Toecap

Midsole Lining

Footbed

Sample weight 0.235 gr.

Practical design, adjustable to every foot

Printed Action Leather

EVA/Rubber

Coolmax Mesh

SJ Hybrid 5MM Safety category EN ISO 20347 - OB / ESD, A, SRC, E





Size range EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 / CM 23.0-27.0



ELECTROSTATIC DISCHARGE (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 35 MegaOhm.



COOLMAX® LINING

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



REMOVABLE INSOLE

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.





WWW.SAFETYJOGGER.COM





CARIN **DE**

Industries:

Catering, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Printed Action Leather			
	Upper: permeability to water vapor		1.2	
	Upper: water vapor coefficient		15.2	
Lining	Coolmax Mesh			
	Lining: permeability to water vapor		28.9	
	Lining: water vapor coefficient		231.3	
Footbed	SJ Hybrid 5MM			
	Footbed: abrasion resistance		400	
Outsole	EVA/Rubber			
	Outsole abrasion resistance (volume loss)		111	
	Outsole slip resistance SRA: heel		0.46	
	Outsole slip resistance SRA: flat		0.52	
	Outsole slip resistance SRB: heel		0.14	
	Outsole slip resistance SRB: flat		0.19	
	Antistatic value		NA	
	ESD value		68	
	Heel energy absorption		31	
Тоесар				
	Impact resistance toecap (clearance after impact 100J)		NA	
	Compression resistance toecap (clearance after compression 10kN)		NA	
	Impact resistance toecap (clearance after impact 200J)		NA	
	Compression resistance toecap (clearance after compression 15kN)		NA	

Sample size:

ENGINEERED IN EUROPE

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



INDUSTRIAL PROFESSIONAL TACTICAL

WWW.SAFETYJOGGER.COM