

SAFETY JOGGER

PROFESSIONAL



SPORTS

ELA 01

Sporty and trendy sneaker for her

Upper	Synthetic Leather
Outsole	PU/Rubber
Toecap	
Midsole	
Lining	Mesh
Footbed	SJ foam footbed
Safety category	EN ISO 20347 - O1 / ESD, SRC
Sample weight	0.336 gr.
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 / CM 23.0-27.0



LGR



LBL



FUX



LIC



MEMORY FOAM

The removable memory foam insole provides extra comfort during stepping and can be exchanged with your own orthopedic sole.



ELECTROSTATIC DISCHARGE (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 35 MegaOhm.



COOLMAX® LINING

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.

REMOVABLE INSOLE

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



SAFETY JOGGER
WORKS

INDUSTRIAL PROFESSIONAL TACTICAL

WWW.SAFETYJOGGER.COM

ENGINEERED
IN EUROPE



SPORTS

ELA 01

Industries:

Catering, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Synthetic Leather			
	Upper: permeability to water vapor	mg/cm ² /h	1.1	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	17.0	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	33.3	≥ 2
	Lining: water vapor coefficient	mg/cm ²	266.5	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	PU/Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	124	≤ 150
	Outsole slip resistance SRA: heel	friction	0.48	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.57	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.15	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	0.32	0.1 - 1000
	ESD value	MegaOhm	74	0.1 - 100
	Heel energy absorption	J	38	≥ 20
Toecap				
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	≥ 13
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	≥ 13
	Impact resistance toecap (clearance after impact 200J)	mm	N/A	≥ 13
	Compression resistance toecap (clearance after compression 15kN)	mm	N/A	≥ 13

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.