

# SAFETY JOGGER

PROFESSIONAL



SPORTS

## JUSTIN 01

Sporty and trendy sneaker for him

Upper	Synthetic Leather
Outsole	PU/Rubber
Toecap	
Midsole	
Lining	Mesh
Footbed	SJ foam footbed
Safety category	EN ISO 20347 - O1 / ESD, SRC
Sample weight	0.378 gr.
Size range	EU 39-47 / UK 6.0-12.0 / US 6.5-13.0 / CM 25.5-31.0



### MEMORY FOAM

The removable memory foam insole provides extra comfort during stepping and can be exchanged with your own orthopedic sole.



### ELECTROSTATIC DISCHARGE (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 35 MegaOhm.



### COOLMAX® LINING

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



### REMOVABLE INSOLE

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

SAFETY JOGGER  
WORKS

INDUSTRIAL PROFESSIONAL TACTICAL

WWW.SAFETYJOGGER.COM

ENGINEERED  
IN EUROPE



SPORTS

## JUSTIN 01

**Industries:**

Catering, Cleaning, Medical

**Environments:**

Dry environment, Extreme slippery surfaces

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
<b>Upper</b>	<b>Synthetic Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	1.1	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	17.0	≥ 15
<b>Lining</b>	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	35.6	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	284.9	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance	cycles	400	≥ 400
<b>Outsole</b>	<b>PU/Rubber</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	125	≤ 150
	Outsole slip resistance SRA: heel	friction	0.44	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.48	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.16	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.20	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	71	0.1 - 100
	Heel energy absorption	J	40	≥ 20
<b>Toecap</b>				
	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	NA	≥ 14

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.