

# SAFETY JOGGER

## PROFESSIONAL



MOVE UP

## SANDY OB

Trendy clog with adjustable velcro strap



Upper	Printed Action Leather
Outsole	EVA/Rubber
Toecap	
Midsole	
Lining	Coolmax Mesh
Footbed	SJ Hybrid 5MM
Safety category	EN ISO 20347 - OB / ESD, A, SRC, E
Sample weight	0.233 gr.
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 / CM 23.0-27.0



### ELECTROSTATIC DISCHARGE (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 35 MegaOhm.



### COOLMAX® LINING

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



### REMOVABLE INSOLE

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

**SAFETY JOGGER**  
WORKS

INDUSTRIAL PROFESSIONAL TACTICAL

WWW.SAFETYJOGGER.COM

ENGINEERED  
IN EUROPE



MOVE UP

## SANDY OB

### Industries:

Catering, Cleaning, Food & beverages, Medical

### Environments:

Dry environment, Extreme slippery surfaces, Uneven surfaces

### Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
<b>Upper</b>	<b>Printed Action Leather</b>			
	Upper: permeability to water vapor		2.7	
	Upper: water vapor coefficient		25.4	
<b>Lining</b>	<b>Coolmax Mesh</b>			
	Lining: permeability to water vapor		14.5	
	Lining: water vapor coefficient		116.1	
<b>Footbed</b>	<b>SJ Hybrid 5MM</b>			
	Footbed: abrasion resistance		400	
<b>Outsole</b>	<b>EVA/Rubber</b>			
	Outsole abrasion resistance (volume loss)		117	
	Outsole slip resistance SRA: heel		0.49	
	Outsole slip resistance SRA: flat		0.46	
	Outsole slip resistance SRB: heel		0.18	
	Outsole slip resistance SRB: flat		0.23	
	Antistatic value		14.3	
	ESD value		34.0	
	Heel energy absorption		42.0	
<b>Toecap</b>	Impact resistance toecap (clearance after impact 100J)		N/A	
	Compression resistance toecap (clearance after compression 10kN)		N/A	
	Impact resistance toecap (clearance after impact 200J)		N/A	
	Compression resistance toecap (clearance after compression 15kN)		N/A	

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:  
38