

### SUNNY DB Sporty and fashionable sneaker for her

Upper	Synthetic Leather
Outsole	EVA/Rubber
Тоесар	
Midsole	
Lining	Mesh
Footbed	Oxy Basic
Safety category	EN ISO 20347 - OB / SRA, E
Sample weight	0.325 gr.
Size range EU 3	35-42 / UK 3.0-8.0 / US 5.5-10.5 / CM 23.0-27.0







### **COOLMAX® LINING**

Coolmax<sup>®</sup> technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



INDUSTRIAL PROFESSIONAL TACTICAL

WWW.SAFETYJOGGER.COM





## SPORTS

# SUNNY **DB**

### Industries:

Catering, Cleaning, Food & beverages, Medical

### **Environments:**

Dry environment

#### **Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347		
Upper	Synthetic Leather					
	Upper: permeability to water vapor	mg/cm²/h	1.1	≥ 0.8		
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	16.8	≥15		
Lining	Mesh					
	Lining: permeability to water vapor	mg/cm²/h	51.4	≥ 2		
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	412.1	≥ 20		
Footbed	Oxy Basic					
	Footbed: abrasion resistance	cycles	400	≥400		
Outsole	EVA/Rubber					
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	135	≤ 150		
	Outsole slip resistance SRA: heel	friction	0.38	≥ 0.28		
	Outsole slip resistance SRA: flat	friction	0.38	≥ 0.32		
	Outsole slip resistance SRB: heel	friction	N/A	≥ 0.13		
	Outsole slip resistance SRB: flat	friction	N/A	≥ 0.18		
	Antistatic value	MegaOhm	N/A	0.1 - 1000		
	ESD value	MegaOhm	N/A	0.1 - 100		
	Heel energy absorption	J	23.0	≥ 20		
Тоесар						
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	≥13		
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	≥13		
	Impact resistance toecap (clearance after impact 200J)	mm	N/A	≥13		
	Compression resistance toecap (clearance after compression 15kN)	mm	N/A	≥13		

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



INDUSTRIAL PROFESSIONAL TACTICAL

WWW.SAFETYJOGGER.COM



Sample size: